
AV PRO CFexpress XT MK2



CFexpress[™] 2.0 | TYPE B

HIGHEST SUSTAINED SPEED CFEXPRESS PERFORMANCE FOR EXTENDED RAW 12K+ VIDEO AND PHOTO PRODUCTION



330 GB | 660 GB | 1320 GB





FEATURES

	CFexpress [™] 2.0	Туре В	001101 101011 001101 101	Extended Endurance Prolonged Lifetime of the Card		
12K+)	Guaranteed Sus Speed of 1480 I	MB/s		Y2 Processor Exceptional Processing Power		
	for RAW 12K+ Producti	on		for RAW Video and Photo Produ	uction	
\approx	Stable Stream [™] Uninterrupted Read/Wri throughout the Card's C	ite Performance apacity		Rock-Solid Build		I
	Advanced Therm Protects the Card again		(4)	Adaptive Power Mana Improved Run Time of the Came		
	Host Power Los	s Protection	(\mathcal{P})	Free Engraving Optio	'n	
	Host Power Los	s Protection		Free Engraving Optio	n	2
	Host Power Loss Data Recovery S on Hard- and Software L	Service ¹		Free Engraving Optio	n	
001101 100101 10010 10010 00 MB/s - 0 MB/s -	Data Recovery S on Hard- and Software L	Service ¹	 ANGELBIRD BRAND X BRAND Y Write Performance 	Free Engraving Optio	n	
0 MB/s 0 MB/s 0 MB/s 0 MB/s 0 MB/s 0 MB/s 0 MB/s 0 MB/s 0 MB/s 0 MB/s	Data Recovery S on Hard- and Software L	Service ¹ Level	- BRAND X - BRAND Y Write Performance	Free Engraving Optio	n	: - - -
0 mB/s 0 mB/s	Data Recovery S on Hard- and Software L	Service ¹ Level MK2 Stable Stream [®] Sustained V Actual Wr Nikon Z 9 [45.7MP 20p RA	- BRAND X - BRAND Y Write Performance	Free Engraving Optio	n	
	Data Recovery S on Hard- and Software L	Service ¹ Level MK2 Stable Stream [®] Sustained V Actual Wr Nikon Z 9 [45.7MP 20p RA	- BRAND X - BRAND Y Write Performance ite Requirements W Burst Lossless ite Requirements	Free Engraving Optio	n	

р r e S S X Т Μ Κ 2

С

MEMORY CARDS

SPECIFICATIONS | ORDERING

General

FORM FACTOR CFexpress[™] Type B

CAPACITIES 330 GB | 660 GB | 1320 GB

UNIT DIMENSIONS 38.5 × 3.8 × 29.8 mm (1.52 × 0.15 × 1.17 in)

UNIT WEIGHT ~ 7 g | 0.25 oz

Technical

INTERFACE CFexpress[™] 2.0 | Type B PCle 3.0 ×2

FEATURES Temperature Sensor, TRIM², ECC, EMS Protection, SMART², Power Management

Performance³

MAXIMUM SPEEDS Read: 1785 MB/s Write: 1600 MB/s

SUSTAINED SPEEDS

Read: 1785 MB/s Write: 1480 MB/s

Reliability

DATA RELIABILITY Built-In EDC / ECC Function

CERTIFICATIONS RoHS, CE, FCC, REACH, KC, RCM

Electrical

DC INPUT VOLTAGE 3.3 V ± 5 %

POWER USAGE

Sleep < 50mW Idle 0.45 W Max 2.40 W

Environmental

SHOCK RESISTANCE Operating: 50 G

VIBRATION RESISTANCE Operating: 15 G

TEMPERATURE RESISTANCE Operating: -10 °C | 70 °C Storage: -20 °C | 85 °C

OPERATING HUMIDITY

5% to 95% Non-Condensing

Warranty⁴

3-Year Limited Warranty

Package Content

• AV PRO CFexpress XT MK2 | Type B

Retail Packaging Details

BOX DIMENSIONS

 $\begin{array}{l} 113 \times 23 \times 132 \text{ mm} \\ (4.45 \times 0.91 \times 5.2 \text{ in}) \end{array}$

BOX WEIGHT

~ 60 g | 2.12 oz

- Data recovery service exclusively provided by Angelbird in Austria.
- ² TRIM and SMART support depending on the OS used.
 ³ Speeds based on internal testing. Actual transfer rates and capacity may vary depending on system hardware and other factors. 4K, 6K, 8K, 12K+ and Full HD support may vary depending on host device, file attributes, and other factors.
- Visit <u>angelbird.com/warranty-activation</u> and activate your
 3-year warranty within 30 days of purchase.

© 2022 Angelbird Technologies GmbH Angelbird is a registered trademark of Angelbird Technologies. All rights reserved.

Other product names used herein are for identification purposes only and may be trademarks of their respective owners. Angelbird disclaims any and all rights in those marks.

Specifications are subject to change without notice. Specifications are provided "as is" without warranty of any kind.

ORDERING INFORMATION

•	Capacity	SKU	EAN	UPC
•	330 GB	AVP330CFXBMK2XT	9120056585922	812937024741
•	660 GB	AVP660CFXBMK2XT	9120056585939	812937024758
•	1320 GB	AVP1T3CFXBMK2XT	9120056585946	812937024765

MEMORY CARDS

