OBV-2800

HD/SD 12-CHANNEL MOBILE VIDEO STUDIO **OBV-2800**

















OBV-2800 is a PPU (portable production unit), designed to fit into the back of a small van to provide complete mobile production facilities. It's a mobile, transportable solution for broadcasters and professionals for both in-studio and on-location productions.

Built around the latest HD / SD switcher, it supports up-to 12 channels of HD/SD-SDI, HDMI or composite video signals. The system is integrated, compact and sturdy with a metal framework for great stability and protection yet provides room for future expansion. With power-efficient modules, OBV-2800 can be powered by a DC 12V supply.

Datavideo OBV-2800 is easy to install and cost-effective.





Live Events



Outdoor Broadcast



In Studio

FEATURES

The OBV-2800 is based on Datavideo SE-2800, 8/12 channels HD/SD digital video switcher and incorporates:

- 2 x TLM-170HR: HD monitors for multiviewer/PGM
- 1 x HDR-70: HD recorders for PGM and AUX
- VSM-100: vectorscope / waveform monitor
- ITC-100: 8-ch intercom / tally system with 8-Ch belt pack
- AM-100: 5-ch audio mixer
- AD-100: audio delay box
- PD-2A: power distributor (8 x DC 12V)
- PD-3: 8-ch power center ■ RP-45: 8-ch CV return video

- 4-ch VP-445 SDI amplifier
- Digital/Analog converter: DAC-50
- Optional PD-4A AC redundant power center
- Optional 30m / 50m all-in-one cable CB-22/23 and cable extender VP-605
- Optional MCU-200: multi-camera controller for Panasonic cameras
- Optional CG-350 HD/SD CG system

All the above items have been designed into two racks with foldable tables for ease of operation in studio, at locations or in a van.

Easy installation into a van with a customized OBV rack base

BENZ VIANO







Remove chairs

Install mounting bracket

Install OBV Rack base

JINBEI AUTOMOTIVE







Remove chairs

Install OBV Rack base

HYUNDAI







Remove chairs

Install OBV Rack base







Roll in the OBV-2800

Cable drums

OB on the go

APPLICATION



Reconvert OBV into a passenger vehicle



OBV-2800 operation in a OB van

V V V V V

FRONT VIEW






REAR VIEW









DIAGRAM


Video Connection



Audio Connection



Tally and Power connection



ACCESSORIES INCLUDED



Intercom belt pack




Tally light indicator



20m 5-Pin intercom cable



1.2m GPI cable



Gooseneck light & microphone



Dual-side headset



Single-side headset



OBV trolley

OPTIONAL ACCESSORIES



4.3" look-back system



DV/HDV CF card recorder



Ball head



Removable hard drive carrier



All in one cable extender



HD/SD 30M or 50M all in one cable with oower



100m SDI repeater



Camera power regulator



SDI to HDMI converter



HDMI to SDI converter



SDI to analog cross converter



SDI to VGA converter

DIMENSION

