

# 7" SD TFT LCD MONITOR TLM-700

16:9/4:3



## FEATURES

- 7" 16:9 wide screen panel
- Resolution: RGB 480X234 pixels
- View angle (V)+50/-40°, (H)+60/-60°
- 2 x Video input
- Brightness, contrast, color, tint adjustable (Tint NTSC only)
- NTSC/PAL auto switching
- 16:9 / 4:3 switchable
- Carry case Included

## REAR VIEW



VIDEO IN-2 VIDEO IN-1

## FEATURES

### Screw for Ball Head

Standard screw mount for fixture to a tripod or the supplied ball head



### Input Source Selector

Two input source selector



### TLM-700 Carrying Case

TLM-700 is supplied with a stylish bespoke carrying case, easy to carry around with supplied accessories



### Sun Shield

Supplied with very useful light weight sun shield



## SPECIFICATIONS

### LCD COMPARISON TABLE

					 	
<b>Screen</b>	TLM-170P	TLM-702HD	TLM-700HD	TLM-700	TLM-434H	TLM-430
<b>Chassis</b>	1 x 17.3" * Tabletop * Tilttable Screen	2 x 7" LCD/Back-Lit LED 3U Rack Mount	1 x 7" Back-Lit LED 1/4 - 20" Thread Hole Mount	1 x 7" TFT LCD 1/4 - 20" Thread Hole Mount	4 x 4.3" TFT LCD 2U Rack Mount	1 x 4.3" TFT LCD 1/4 - 20" Thread Hole Mount
<b>Resolution</b>	1920x1080	800x480	800x480	480x234	480x272	480x272
<b>Video Inputs</b>	2 x Composite Video, 1 x S-Video, 1 x HD Component YUV, 1 x HD/SD-SDI, 2 x HDMI	2 x HD Component 2 2x HD/SD-SDI, YUV, 2 x HDMI, 2 x Composite Video	1 x Composite Video, 1 x HD/SD-SDI, 1 x HD Component YUV, 1 x HDMI	2 x Composite Video	4 x HD/SD-SDI, 4 x HDMI	4 x Composite Video
<b>Loop Through</b>	1 x 3G/HD/SD-SDI, 2 x Composite Video	N/A	N/A	N/A	4 x HD/SD-SDI	N/A
<b>Supported Input Resolutions</b>	1080p (23.98/24/25/30/50/59.95/60Hz), 1280x720p (50/60 Hz), 720x480i (NTSC), 1080i (50/59.94/60Hz), 1280x720p (50/59.94/60 Hz), 720x480i (NTSC), 720x576i (PAL)	1920x1080i (50/60Hz), 1280x720p (50/60 Hz), 720x480i (NTSC), 720x576i (PAL)	1920x1080i (50/60Hz), 1280x720p (50/60 Hz), 720x480i (NTSC), 720x576i (PAL)	720x480i (NTSC), 720x576i (PAL)	1920x1080i (50/60Hz), 1280x720p (50/60 Hz), 720x480i (NTSC), 720x576i (PAL)	720x480i (NTSC), 720x576i (PAL)
<b>Aspect Ratio</b>	16:9, 4:3	16:9, 15:9, 4:3	16:9, 15:9, 4:3	16:9, 4:3	16:9, 4:3	16:9, 4:3
<b>NTSC/PAL Tally</b>	Auto-Detect Live (Red) / Cued (Amber)	Auto-Detect Live (Red) / Cued (Amber)	Auto-Detect Live (Red) / Cued (Amber)	Auto-Detect N/A	Auto-Detect Live (Red) / Cued (Amber)	Auto-Detect Big Tally Light
<b>Audio</b>	* Plays Embedded Audio in 3G/HD/SD-SDI and HDMI * 4 x Mono RCA Inputs * Stereo Speakers	* Audio Presence Indicator * Audio Level Meter * 2 x Stereo Headphone Mini Jack	* Audio Presence Indicator * Audio Level Meter * Stereo Headphone Mini Jack	N/A	* 4 x Stereo Headphone Mini Jacks * Embedded Audio Peak Meter	N/A
<b>Special Features</b>	* 3G-SDI Support * Picture-in-Picture * Blue Only * Audio Level Indicator * Safe Frame	* Blue Only * Safe Frame * VITC Time Code Display	* Blue Only * Safe Frame * VITC Time Code Display * Can Use Batteries (Not Included) as Power Source	* Carrying Case Included * Sunshade Included	* Blue Only * Embedded Time Code Indicator * Safe Frame	* Can powered by DC adaptor; Sony batteries or D-TAP. * TLM-43LB Camera look back system (with RMC-200 and control cable)
<b>Consumption</b>	DC 12V, 30 watts	DC 12V, 30 watts	DC 12V, 18 watts	DC 12V, 6 watts	DC 12V, 15 watts	DC 12V, 6 watts