



THE NEXT GENERATION POWER SOLUTION FOR CINEMA AND BROADCAST

[www.coreswx.com](http://www.coreswx.com)



Rated for 2K cycles with a 2-year warranty.



Able to communicate with cameras as well as chargers; supports both one-wire, and two-wire protocols.



Hibernation

The packs go to sleep/hibernate when there is no battery usage or movement after a 48 hour period. Once the battery is picked up, the battery pack awakens.



UN38.3 Certified

UN38.3 certified & travel safe battery pack to make customers traveling experience go as smooth as possible.



LED Gauge

With the display on the side of all brick battery packs, users can easily glance at remaining battery capacity.



Compatible Charging

Our packs are the most charger compatible in the industry which allows users with existing charger hardware to continue using their charger.



Smart Tap

Integrated "Smart" p-tap connector to allow users to power any 12v DC device while also receiving all battery data from the port.



USB Power

NEO battery packs offer a 5v USB port for any accessory on set that may use USB or to charge your mobile devices.



High Current Delivery

Neo 16 Amp Peak with 12 Amp draw.



RFID

View your battery vitals from mobile app or RFID reader.



Rubberized Housing

The packs are encased in an over-moulded, non-slip rubberized housing to help provide cell protection against accidental impacts.




Storage Mode

To protect self-discharge and help comply with travel regulations, Core SWX incorporates a storage mode into all brick battery packs.



Firmware Upgradeable

Through USB Neo packs are now firmware upgradeable.



Modular Build

All Hypercore packs have a modular build design. This reduces wiring and ensures maximum build integrity.



Runtime LCD

New multi-purpose backlit LCD. It displays runtime based on a 25w load, remaining runtime once connected to a device, and remaining charge time when on a charger.

# NEO DESIGN

## and exclusive features





1000178500000

HYPERCOLOR  
**NEO 9**  
MINI

HDMI

HDMI

HD-SDI

DC-IN

IRONLAD

TERACOM

# NEO MODELS



## V-MOUNT

LI-ION 14.8V  
6600mAh 98Wh  
SMART TAP & USB

NEO-9S



## 3-STUD

LI-ION 14.8V  
6600mAh 98Wh  
SMART TAP & USB

NEO-9AG

# VOLT BRIDGE ID



## RFID

View your battery vitals from mobile app or RFID reader.





# CORE<sup>SWX</sup> *Driven*

Tested and trusted by cinema professionals throughout the globe.



**holdan**

© Holdan Ltd Core NEO v1 11/19

Holdan Limited  
Brookfield House, Brookfield Industrial Estate  
Peakdale Road, Glossop, Derbyshire, SK13 6LQ United Kingdom

Phone: +44 (0)1457 851000 Email: [sales@holdan.co.uk](mailto:sales@holdan.co.uk)

[www.holdan.co.uk](http://www.holdan.co.uk)