



PARALINX.NET

PARALINX

- REALTIME WIRELESS VIDEO
- RANGE OF UP TO 2000FT
- RECEIVER 60% SMALLER
- SDI AND HDMI INPUTS ON TRANSMITTER
- 6-28V 2-PIN POWER INPUT
- OPTIONAL BATTERY PLATES, ANTENNAS, AND MOUNTING BRACKETS

Technical Specifications

- COMPATIBLE WITH TERADEK BOLT 2000, TERADEK SIDEKICK, & PARALINX TOMAHAWK
- Maximum Range of 2000ft / 600m
- Video Input: 3G-SDI and HDMI
- Video Output: 3G-SDI
- Realtime Monitoring - less than 1ms delay
- Operates on unlicensed 5GHz spectrum (5.1-5.8GHz)
- Certified FCC, CE, MIC
- Multi-receiver capable - use up to 4 receivers per transmitter



ULTRALIGHT
REALTIME
WIRELESS
MONITORING



PRODUCT INFO
SPRING 2017



- AFFORDABLE
- RANGE UP TO 300FT
- REALTIME WIRELESS HD VIDEO
- ULTRALIGHT & COMPACT
- 3G-SDI OR HDMI TRANSMITTER & RECEIVER
- OPTIONAL ATTACHABLE BATTERY PLATES & MOUNTING BRACKETS

Technical Specifications

- NOW COMPATIBLE WITH TERADEK SIDEKICK
- Maximum Range 300ft / 100m
- MIX AND MATCH 3G-SDI or HDMI input / output options
- Transmits visually lossless video up to 1080p60
- Realtime Monitoring - less than 1ms delay
- Operates on unlicensed 5GHz spectrum (5.1-5.8GHz)
- Certified FCC, CE, MIC
- Multi-receiver capable - use up to 4 receivers per transmitter
- 7-17v Input voltage range w/2-pin Power Connector on SDI model
- Threaded holes for attaching wide array of battery plates



- REALTIME WIRELESS HD VIDEO
- RANGE OF UP TO 700FT
- 3G-SDI OR HDMI TRANSMITTER
- 7-17V 2-PIN POWER INPUT
- OPTIONAL BATTERY PLATES, ANTENNAS AND MOUNTING BRACKETS

Technical Specifications

- NOW COMPATIBLE WITH TERADEK SIDEKICK
- Maximum Range of 700ft / 220m
- Input Options: 3G-SDI or HDMI
- Output Options: Dual 3G-SDI
- Realtime Monitoring - less than 1ms delay
- Operates on unlicensed 5GHz spectrum (5.1-5.8GHz)
- Certified FCC, CE, MIC
- Multi-receiver capable - use up to 4 receivers per transmitter



- ULTRA COMPACT & LIGHTWEIGHT
- LONG RANGE FOR MOBILE ACTION MONITORING
- REALTIME WIRELESS VIDEO AND AUDIO
- PASS REGULATED 5V POWER TO A GOPRO
- INTEGRATED LP-E6 BATTERY PLATE
- RUGGED MACHINED-ALUMINUM CHASSIS

Technical Specifications

- Maximum Range 1000ft / 300m
- 100g Transmitter - perfect for mobile action mounts
- 3G-SDI or HDMI receiver output options
- Transmits visually lossless video up to 1080p30 / 1080i60
- Realtime Monitoring - less than 1ms delay
- Operates on unlicensed 5GHz spectrum (5.1-5.8GHz)
- Certified FCC, CE, MIC
- Multi-receiver capable - use up to 4 receivers per transmitter
- 7-17V Input voltage on Battery Plate and 5V 2A through USB
- 2-pin Power Connector on SDI Rx w/7-17V DC input
- Threaded 1/4"-20 hole for attaching mounting accessories

